

StealthMounts®

Tool Mounts

PROUDLY MADE IN THE UNITED KINGDOM

How to use

Mount to under side of shelf or similar horizontal surface, using three suitable screws or rivets (not supplied). To make installation easier, align base slot to front of surface (towards you). Ensure mount is turned fully so that the retaining pins are in, then slide compatible M12® tool fully onto the mount so that it is all the way in, once located, twist tool to engage retaining pins. If tool is not fully inserted into mount, twisting may not be possible or damage may occur if forced. When detaching, twist tool in opposite direction to fully retract pins then pull straight downwards to detach tool. Do not force, if pins catch on tool, raise up and wiggle then pull straight down (if you pull at an angle, the tool is more likely to remain attached to a retaining pin).

Precautions

Do not over-tighten fixings. Check mount integrity prior to use and do not use if damaged. Harsh environments may reduce strength of mount. Mount does not guarantee safe or compliant storage of tool, local regulations must be observed where applicable. Fit in a suitable location where failure (such as broken or separating mount) cannot cause harm or damage if tool falls. Mount may separate under excessive load, but can usually be reassembled. Do not use at height. Do not force mount by twisting, or force into a tool. For some tools, the alignment is more critical and gentle 'wiggling' may be required to attach and detach tool. Not intended for mobile or vehicle use. Liability limited to MSRP of this product. ® Registered trademarks are property of their respective owners.

